

Page 1 of 11 Product: Stihl Fuel Stabiliser Issue Date: 21st Febrauary 2023

Revision: 1.0

SAFETY DATA SHEET

SECTION 1 IDENTIFICATION: PRODUCT IDENTIFIER/CHEMICAL **IDENTITY**

1.1 PRODUCT IDENTIFIER: Stihl Fuel Stabiliser

7004 881 9400 1.2 PRODUCT CODE:

1.3 RELEVANT IDENTIFIED USES OF THE MIXTURE AND USES ADVISED AGAINST:

RELEVANT IDENTIFIED USES: Storage additive for fuel.

None known. **RESTRICTIONS ON USE:**

1.4 DETAILS OF THE SUPPLIER OF THE SAFETY DATA SHEET:

SUPPLIER NAME: Stihl Pty Ltd (ABN: 76 004 881 145),

5 Kingston Park Court, Knoxfield, Victoria, Australia, 3180 ADDRESS:

9 Bishop Browne Place, East Tamaki, Auckland, New Zealand, 1730.

E-MAIL: csc@stihl.com.au; info@stihl.co.nz **TELEPHONE NUMBER:** +61 3 9215 6666 (NZ: +64 9262 4000)

1.5 EMERGENCY TEL. NUMBER: Poisons Information Centre (Aust 131 126; NZ 0800 764 766)

1.6 HSNO DETAILS:

HSNO APPROVAL NUMBER: HSR002581

HSNO GROUP TITLE: Fuel Additives (Combustible) Group Standard 2020

SECTION 2 – HAZARD(S) IDENTIFICATION

2.1 CLASSIFICATION OF THE HAZARDOUS CHEMICAL:

GHS CLASSIFICATION HAZARD

CLASS & CATEGORY: Under the Model Work Health and Safety Regulations the product would be

rated as Hazardous:

Flammable Liquids - Category 4 Aspiration Hazard - Category 1

2.2 LABEL ELEMENTS INCLUDING PRECAUTIONARY STATEMENTS:

SIGNAL WORD: Danger

PICTOGRAMS:

H227 - Combustible liquid.

H304 - May be fatal if swallowed and enters airways.

AUH066 - Repeated exposure may cause skin dryness or cracking.

PRECAUTIONARY STATEMENTS:

HAZARD STATEMENTS:

PREVENTION: P102 - Keep out of reach of children.

P103 - Read carefully and follow all instructions.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other

ignition sources. No smoking.

P280 - Wear protective gloves/protective clothing/eye protection/face protection/

hearing protection.

RESPONSE: P101 - If medical advice is needed, have product container or label at hand.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTRE (phone

Australia 131 126; New Zealand 0800 764 766)/doctor/physician.

P331 - Do NOT induce vomiting.

P370+P378 - In case of fire: Use carbon dioxide, alcohol-resistant foam, dry

chemical or water spray.

P403 - Store in a well-ventilated place. STORAGE:

P405 - Store locked up.

Page 2 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 2 – HAZARD(S) IDENTIFICATION Continued

DISPOSAL: P501 - Dispose of contents/container in accordance with local regulations.

2.3 OTHER HAZARDS:

This is a Schedule 5 Poison. Due to the presence of hydrocarbon solvent there is a possibility of organ system damage. The presence of the solvent component suggests that the product may be irritating to the eyes and respiratory system. Continued inhalation of vapours may also lead to drowsiness and dizziness. The product is a combustible liquid and will potentially form flammable/explosive mixtures in air. There may be static discharge issues with the product in large scale operations that could lead to a fire. People with pre-existing skin conditions, such as eczema or dermatitis, should take precautions so as not to exacerbate the condition. As for all chemical products, persons should not expose open wounds, cuts, abrasions or irritated skin to this material.

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS	CAS NUMBER	Concentration % W/W	GHS Classification*
Distillates, petroleum, hydrotreated light	64742-47-8	> 90%	Flam Liq 4 - H227 Asp Haz 1 - H304
Complex mixture of additives	Not Applic	To 100%	AUH066 Not Applic

SECTION 4 - FIRST AID MEASURES

4.1 DESCRIPTION OF NECESSARY FIRST AID MEASURES:

INGESTION:

Not Applic = Not Applicable

Rinse mouth out with water. If swallowed, do NOT induce vomiting. For advice, contact the Poisons Information Centre (phone Australia 131 126; New Zealand 0800 764 766) or a doctor at once. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. Within 6 hours of ingestion, if delayed symptoms, such as a fever greater than 38.3°C, shortness of breath, chest congestion or continued coughing/wheezing occurs transport immediately to a medical facility. As the product is hydrocarbon based and of low viscosity (3cSt @ 40°C), if ingested seek urgent medical assistance.

* Please see Section 15 of this SDS for the full text description of the Label Elements.

EYE:

If in eyes, hold eyelids apart and flush the eye immediately with large amounts of running water. Continue flushing for at least 15 minutes or until advised to stop by a doctor. Check for contact lenses. If there are contact lenses, these should be removed after several minutes of rinsing by the exposed person or medical personnel if it can be done easily. After flushing, if irritation develops or persists, seek medical assistance.

SKIN CONTACT:

If skin or hair contact has occurred remove any contaminated clothing and footwear, wash skin or hair thoroughly with soap and water. As the product is rated as Repeated exposure may cause skin dryness or cracking, if irritation develops or persists, consult a doctor.

Page 3 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 4 – FIRST AID MEASURES Continued

INHALATION:

If a person is affected by inhaling the product, remove the patient from further exposure into fresh air, if safe to do so. If providing assistance, avoid exposure to yourself - only enter contaminated environments with adequate respiratory equipment, once environment has been assessed for flammable vapours. Once removed, lay patient down in a well-ventilated area and reassure them whilst waiting for medical assistance. If not breathing, provide artificial respiration and seek immediate medical assistance. If unconscious, place in a recovery position and seek immediate medical assistance. If the person is experiencing respiratory symptoms: such as dizziness or uncoordination, immediately call a Poisons Information Centre or a doctor while waiting for medical assistance to arrive.

PROTECTION FOR FIRST AIDERS:

No personnel shall place themselves in a situation that is potentially hazardous to themselves. Assess the scenario for PPE requirements before entering. Assess environment for flammable vapours before entering. Never enter an environment with a flammable atmosphere. Do not enter contaminated area without a respirator. As the product is hydrocarbon based and of low viscosity, if the person has ingested the product, DO NOT use direct mouth-to-mouth resuscitation techniques. Always ensure that you are wearing gloves when dealing with first aid procedures involving chemicals and/or blood.

FIRST AID FACILITIES:

Eye wash fountain and safety showers are recommended in the area where the product is used.

ACUTE:

4.2 MOST IMPORTANT SYMPTOMS & EFFECTS, BOTH ACUTE & DELAYED, CAUSED BY EXPOSURE:

Ingestion or inhalation of vapours may lead to irritation of the mouth and respiratory tract. Symptoms may include a burning sensation in the nose and throat, coughing or difficulty breathing. Ingestion may lead to nausea and diarrhoea. If material is aspirated into the lungs it may exhibit as coughing, wheezing, congestion or fever. Inhalation of high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Eve contact may lead to localised burning, redness and tearing. Skin contact may lead to redness or itching.

CHRONIC:

Repeated or prolonged skin contact may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. Repeated or prolonged skin contact may also aggravate/exacerbate existing skin conditions, such as dermatitis.

ADVICE TO DOCTOR:

4.3 INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NECESSARY: Treat symptomatically. As the product is hydrocarbon based and of low viscosity, if vomiting has occurred after ingestion, the patient should be monitored for adverse effects to ensure that the product has not aspirated into Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Inhalation of high vapour concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea.

SECTION 5 - FIRE FIGHTING MEASURES

5.1 EXTINGUISHING MEDIA:

SUITABLE MEDIA: Use extinguishing media appropriate for surrounding fire. Use carbon dioxide,

alcohol-resistant foam, dry chemical or water spray. Spray down fumes

resulting from fire.

UNSUITABLE MEDIA: Avoid using full water jet directed at residual material that may be burning.

Water may cause splattering on hot residues. Product will float on water.

5.2 SPECIAL HAZARDS ARISING FROM THE SUBSTANCE OR MIXTURE:

COMBUSTION HAZARDS: Combustion may produce oxides of carbon, as well as smoke and irritating

vapours.

Page 4 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 5 – FIRE FIGHTING MEASURES Continued

5.3 ADVICE FOR FIREFIGHTERS:

FIRE: This product is a Class C1 combustible liquid with a typical flash point of >61°C

 $^-$ <93°C. The vapour is heavier than air and will spread along the ground and may accumulate in low points or depressions. Therefore, ignition may occur well away from the point of release of the material. Keep storage tanks,

pipelines, fire exposed surfaces, etc. cool with water spray.

HAZCHEM CODE: Not applicable.

EXPLOSION: No information to indicate that the product is an explosion hazard; though the

solvent component may form an explosive mixture with air. Note: Under the WHS legislation, this product is rated as Flammable Liquid - Category 4, with a typical Flash point of >61°C - <93°C. Extinguish all sources of flame or spark.

Closed containers may explode when exposed to extreme heat.

PROTECTIVE

EQUIPMENT: In the event of a fire, wear full protective clothing and self-contained breathing

equipment with full-face piece operated in the pressure demand or other

positive pressure mode.

SECTION 6 – ACCIDENTAL RELEASE MEASURES

6.1 PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

PERSONAL PROTECTION:

For small spills, wear Nitrile gloves, glasses/goggles, boots and full-length clothing. During routine operation for a small spill in the open a respirator is not required. However, if mists or vapours are generated, an approved organic vapour/particulate respirator is required. For large spills, or in confined spaces, a full chemically resistant body-suit is recommended and the atmosphere must be evaluated for oxygen deficiency and whether the atmosphere is flammable. If in doubt about potential oxygen deficiency, wear self-contained breathing apparatus. Never enter an environment with a flammable atmosphere.

CONTROL MEASURES:

Ventilate area and extinguish and/or remove all sources of ignition. CAUTION: Vapour may form an explosive mixture with air. Never enter a spill area unless you know the vapours have dissipated to make the area safe. Stop the leak if safe to do so. Caution: The spilled product will be slippery. Avoid contact with the spilled material.

EMERGENCY PROCEDURES: In the event of a spill or accidental release, notify the relevant authorities in accordance with all applicable regulations.

6.2 ENVIRONMENTAL PRECAUTIONS:

SPILL ADVICE:

Do not allow product to enter drains, surface water, sewers or watercourses - inform local authorities if this occurs. Take precautions against static discharge. Ensure all equipment is grounded and use non-sparking tools during clean up operations.

6.3 METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP:

CONTAINMENT:

Contain the spill and absorb with a proprietary absorbent material, sand or earth. Caution: The spilled product will be slippery. Be careful of static discharges and/or sparking during clean up. For large spills prepare a bund/barrier/dyke ahead of the spill to confine the spill and allow later recovery. If there is the possibility of spills to enter drains, surface water, sewers or watercourses ensure bunding, or that drains are covered, to minimise the potential for this to occur.

Page 5 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 6 – ACCIDENTAL RELEASE MEASURES Continued

CLEANING PROCEDURES:

Having contained the spill, as mentioned above, collect all material quickly and place used absorbent in suitable containers. Be careful of static discharges and/or sparking during clean up. Use only non-sparking tools during cleaning operations. Caution: The spilled product will be slippery. Follow local regulations for the disposal of waste. For large spills that have been bunded, the material can be pumped, using flammable liquid equipment, into vessels and returned for reprocessing or destruction. Personnel must wear gloves, goggles or glasses, boots and full-length clothing during cleaning procedures. Wash contaminated area and objects with detergent and water after spill has been cleared. Rinse the cleaned area with water. Do not allow wash water or rinsings to enter drains, surface water, sewers or water courses.

SECTION 7 – HANDLING AND STORAGE, INCLUDING HOW THE CHEMICAL MAY BE SAFELY USED

7.1 PRECAUTIONS FOR SAFE HANDLING:

SAFE HANDLING:

Avoid contact with the product by using appropriate protective equipment such as gloves, glasses or goggles and full-length clothing. Extinguish any potential sources of ignition before using as flammable vapours will be generated during application. Avoid breathing mists or vapours. Do not smoke when handling the material. Prevent small spills and leakage to avoid slip hazards. Properly dispose of any contaminated rags or cleaning materials in order to prevent fire hazards. Eating, drinking, and smoking should be prohibited in the area where this material is handled, stored and processed. Workers should follow good personal hygiene practices, such as washing hands before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. Keep containers tightly closed when not in use. Prevent product from entering waterways, drains or sewers. There is the potential for electrostatic accumulation in the product. As a precaution, containers should always be earthed before dispensing commences. Please note that flammable mixtures may be formed when residual material remains in empty containers.

7.2 CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATABILITIES:

SAFE STORAGE:

Classified as a Flammable Liquids Category 4 (Combustible Liquid) under the WHS Regulations (Flash Point >61 $^{\circ}$ C - < 93 $^{\circ}$ C). Store in a dry, well ventilated area away from direct sunlight, ignition sources, oxidising agents, foodstuffs and clothing. Keep containers closed when not in use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Store only in original containers. It is recommended that the product be stored below 25 $^{\circ}$ C.

INCOMPATIBILITIES: Oxidising substances including strong acids.

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION

8.1 EXPOSURE CONTROL MEASURES:

EXPOSURE LIMIT VALUES: Exposure standards for the product have not been established. The following

values are applicable for the individual components:

Distillates, petroleum, hydrotreated light (Manufacturer recommendation):

TWA: 790 mg/m³ (White Spirits)

8.2 BIOLOGICAL

MONITORING: No data available.

8.3 CONTROL BANDING: No data available.

Page 6 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 8 – EXPOSURE CONTROLS & PERSONAL PROTECTION Cont'd

8.4 ENGINEERING CONTROLS:

ENGINEERING CONTROLS: Special ventilation is not normally required when using this product in normal

use scenarios. However, at elevated temperatures, or in confined spaces mists or vapour may be generated and local exhaust ventilation should be provided to maintain airborne concentration levels below the nominated exposure standard and at an acceptable level that does not cause irritation. PLEASE NOTE: Due to the flammable nature of the product, if there is a necessity to use ventilation equipment it should not be a potential source of ignition for any vapours

generated.

8.5 INDIVIDUAL PROTECTION MEASURES:

EYE & FACE PROTECTION: Wear safety glasses/goggles to avoid eye contact when handling. If there is a

risk of splashing during use, a full face shield is recommended. Use eye

protection in accordance with AS 1336 and AS 1337.

SKIN (HAND) PROTECTION: If there is the chance of contact with the material wear gloves to provide hand

protection. Nitrile rubber gloves are recommended.

SKIN (CLOTHING)

PROTECTION: During normal operating procedures, long sleeved clothing is recommended to

avoid skin contact. Soiled clothing should be washed with detergent prior to re-

use.

RESPIRATORY PROTECTION: During routine operation a respirator is not required. However, if mists or

vapours are generated, an approved half face organic vapour/particulate respirator is required. Use respirators in accordance with AS 1715 and AS

1716.

THERMAL PROTECTION: Not applicable.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

9.1 PHYSICAL AND CHEMICAL PROPERTIES:

APPEARANCE: Red liquid.

ODOUR: Characteristic hydrocarbon solvent odour.

ODOUR THRESHOLD: No data available.

pH: Not applicable.

MELTING/FREEZING POINT: No data available.

INITIAL BOILING POINT: Typically 82.2°C

BOILING RANGE (°C): No data available.

FLASHPOINT (°C): Typically >61°C - <93°C.

EVAPORATION RATE: > 1 BuAC = 1.

FLAMMABILITY LIMITS (%): Lower Explosive Limit: 0.8%; Upper Explosive Limit: 7.0%.

VAPOUR PRESSURE (kPa): 13.0. VAPOUR DENSITY (Air = 1): > 1.

RELATIVE DENSITY: Typically 0.8

SOLUBILITY IN WATER(g/L): Insoluble in water.

PARTITION COEFFICIENT: No data available for n-octanol/water.

AUTO-IGNITION TEMP (°C): No data available. DECOMPOSITION TEMP (°C): No data available. VISCOSITY (cSt @ 100°C): No data available VISCOSITY (cSt @ 40°C): Typically 3.0.

Page 7 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 10 - STABILITY AND REACTIVITY

10.1 REACTIVITY: The product does not pose any further reactivity hazards other than those listed

in the following sub-sections.

10.3 POSSIBILITY OF **HAZARDOUS REACTIONS:**

10.2 CHEMICAL STABILITY: Stable under recommended storage and handling conditions (see section 7).

Keep away from strong oxidising agents, such as strong acids, chlorates,

nitrates and peroxides. Hazardous polymerisation does not occur.

10.4 CONDITIONS TO AVOID: The product has a relatively low flash point of >61°C - <93°C. Avoid ignition

sources including heat and sparks. Observe the usual precautionary measures for handling chemicals. Do not heat the container or leave the container open

when not in use.

10.5 INCOMPATIBLE

MATERIALS: Strong oxidising agents including strong acids.

10.6 HAZARDOUS DECOMPOSITION

PRODUCTS: Hazardous decomposition products are not expected to form during normal

storage requirements. See Section 5.2 for Hazardous Combustion products.

SECTION 11 – TOXICOLOGICAL INFORMATION

11.1 INFORMATION ON TOXICOLOGICAL EFFECTS:

The product is a mixture and test data is not available for the product as a whole.

Distillates, petroleum, hydrotreated light (IUCLID)

Oral - LD₅₀ (Rat): > 5000 mg/kg Dermal - LD₅₀ (Rabbit): > 2000 mg/kg

11.2 SWALLOWED: The hydrocarbon component means this is a Schedule 5 Poison. As the

product is hydrocarbon based and the viscosity is low, caution should be taken in respect to aspiration into the lungs. Small amounts of this product aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. Ingestion of large amounts may lead to nausea and vomiting. During normal usage ingestion should not be a means of

exposure.

11.3 SKIN CORROSION/

IRRITATION: This product is rated as repeated exposure may cause skin dryness or cracking

based on the available data and the known hazards of the components. Correct handling procedures incorporating appropriate protective clothing and gloves should minimise the risk of skin irritation. People with pre-existing skin conditions, such as dermatitis, should take extreme care so as not to

exacerbate the condition.

11.4 SERIOUS EYE DAMAGE/

IRRITATION: This product is not expected to exhibit Eye Irritation or Serious Damage/

Corrosivity based on the available data and the known hazards of the components. May be mildly irritating to the eyes. Symptoms may include localised burning, redness and tearing. Correct handling procedures incorporating appropriate eye protection should minimise the risk of eye

irritation.

11.5 RESPIRATORY OR

This product is not expected to be a skin sensitiser, based on the available data SKIN SENSITISATION:

and the known hazards of the components. This product is not expected to be a respiratory tract sensitiser, based on the available data and the known hazards

of the components.

11.6 GERM CELL

MUTAGENICITY: This product is not expected to be mutagenic, based on the available data and

the known hazards of the components.

11.7 CARCINOGENICITY: This product is not expected to be a carcinogen based on the available data

and the known hazards of the components.

Page 8 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 11 – TOXICOLOGICAL INFORMATION Continued

11.8 REPRODUCTIVE

TOXICITY:

This product is not expected to be a reproductive hazard based on the available

data and the known hazards of the components.

11.9 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

SINGLE EXPOSURE:

There is no data available for the product as a whole. This product contains volatile hydrocarbon components, hence inhalation of vapours or mist (generated at elevated temperatures or by mechanical action) may cause irritation to the nose and throat. Inhalation of high concentrations may cause central nervous system depression resulting in headaches, dizziness and nausea. Exposure to high levels of hydrocarbon solvent vapours may impact on the liver and kidneys.

11.10 SPECIFIC TARGET ORGAN TOXICITY (STOT) -

REPEATED EXPOSURE:

This product is not expected to cause organ damage from prolonged or repeated exposure based on the available data and the known hazards of the

components.

11.11 ASPIRATION HAZARD: This product is rated as an aspiration hazard - May be fatal if swallowed and enters airways. Small amounts of liquid aspirated into the lungs during ingestion or from vomiting may cause chemical pneumonitis or pulmonary oedema. This can be fatal. As the product is hydrocarbon based, if the product has been ingested or vomiting has occurred after ingestion, the patient must seek urgent medical attention and should be monitored for adverse effects.

11.12 OTHER INFORMATION: No additional information is available.

SECTION 12 - ECOLOGICAL INFORMATION

12.1 ECOTOXICITY: There is no data available for the product as a whole. Based upon the data as

supplied, the product is not expected to be harmful to the environment

12.2 PERSISTENCE &

DEGRADABILITY:

Based on the available data and the known hazards of the components, the solvent constituents are expected to be inherently biodegradable, however the

product contains components that may persist in the environment.

12.3 BIOACCUMULATIVE

POTENTIAL:

There is no data available for the product as a whole.

12.4 MOBILITY IN SOIL:

There is no data available for the product as a whole. The solvent component is relatively volatile and will evaporate to the air if released to the environment.

12.5 OTHER ADVERSE

EFFECTS:

There is no data available for the product as a whole. The product will float on

water and the solvent component will evaporate into the air.

SECTION 13 - DISPOSAL CONSIDERATIONS

13.1 DISPOSAL METHODS: PRODUCT:

The product should not be released to the environment, so any unused material should be recycled wherever possible or be disposed of as hazardous waste at an appropriate collection depot. The product is also suitable for incineration at very high temperatures to prevent formation of undesirable combustion products. Spilled product that cannot be recovered should be absorbed and then shovelled into a suitable waste container, such as a plastic drum and then be treated as a solid waste. Follow Government regulations for disposal of such waste. All unused, waste or spilled product must be taken for recycling or disposal by suitably licensed contractors in accordance with Government regulations. Note: Waste product must be handled as a Combustible liquid.

Page 9 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 13 – DISPOSAL CONSIDERATIONS

CONTAINERS:

Empty containers may contain residual product. CAUTION: Residues are combustible and will ignite with a source of ignition. Containers should be completely drained in a well ventilated area where vapours cannot accumulate and then stored until reconditioned or disposed of. Empty containers should be taken for recycling or disposal through suitably licensed contractors in accordance with Government regulations. As containers may contain combustible residues, they should not be pressurised, cut by a grinder, drilled or exposed to heat, flames or other sources of ignition. Closed containers when exposed to such conditions/treatment may explode causing serious injury.

SECTION 14 – TRANSPORT INFORMATION

This product is not regulated for land, sea or air transportation.

14.1 LAND (ADG Code):

UN NUMBER: Not applicable

UN PROPER SHIPPING

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

ENVIRONMENTAL

HAZARDS: Not applicable

SPECIAL PRECAUTIONS

FOR USER: Not applicable HAZCHEM CODE: Not applicable

14.2 SEA (IMDG):

UN NUMBER: Not applicable

UN PROPER SHIPPING

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

ENVIRONMENTAL

HAZARDS: Not applicable

SPECIAL PRECAUTIONS

FOR USER: Not applicable

14.3 AIR (IATA):

UN NUMBER: Not applicable

UN PROPER SHIPPING

NAME: Not applicable

TRANSPORT HAZARD

CLASS(ES): Not applicable PACKAGING GROUP: Not applicable

ENVIRONMENTAL

HAZARDS: Not applicable

SPECIAL PRECAUTIONS

FOR USER: Not applicable

Page 10 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 15 - REGULATORY INFORMATION

15.1 SAFETY, HEALTH AND ENVIRONMENTAL REGULATIONS:

APPLICABLE REGULATIONS:

SUSMP: Schedule 5 (S5)

All ingredients are on the AllC.

MONTREAL PROTOCOL: Not applicable. STOCKHOLM CONVENTION: Not applicable. ROTTERDAM CONVENTION: Not applicable. BASEL CONVENTION: Not applicable.

INTERNATIONAL CONVENTION FOR THE PREVENTION OF POLLUTION FROM

SHIPS (MARPOL): Not applicable.
OTHER REGULATORY INFORMATION:

GHS CLASSIFICATION HAZARD CLASS & CATEGORY

AND HAZARD STATEMENT: Flammable Liquids Category 4; H227 - Combustible liquid.

Aspiration Hazard Category 1; H304 - May be fatal if swallowed and enters

airway.

AUH066 - Repeated exposure may cause skin dryness or cracking.

HSNO APPROVAL NUMBER: HSR002581

HSNO GROUP TITLE: Fuel Additives (Combustible) Group Standard 2020

SECTION 16 – ANY OTHER RELEVANT INFORMATION

SDS INFORMATION:

Date of SDS Preparation: 21st February 2023 **Revision:** 1.0

REVISION CHANGES: Review against GHS 7 and update.

ACRONYMS:

SUSMP Standard for the Uniform Scheduling of Medicines and Poisons

CAS Number Chemical Abstracts Service Registry Number

EINECS European Inventory of Existing Commercial Chemical Substances

UN Number United Nations Number

OSHA Occupational Safety and Health Administration

ACGIH American Conference of Governmental Industrial Hygienists HSE-WEL Health and Safety Executive - Workplace Exposure Limit

EH40 EH40/2005 Workplace Exposure Limits
IMDG International Maritime Dangerous Goods
IATA International Air Transport Association

IUCLID International Uniform Chemical Information Database RTECS Registry of Toxic Effects of Chemical Substances

%W/W Percent weight for weight

OECD Organisation for Economic Co-Operation and Development

ADG Code Australian Code for the Transport of Dangerous Goods by Road and Rail

HAZCHEM Code Emergency action code of numbers and letters which gives information to emergency services

NOHSC National Occupational Health and Safety Commission
AICIS Australian Industrial Chemicals Introduction Scheme

NICNAS National Industrial Chemicals Notification & Assessment Scheme

IMAP Inventory Multi-Tiered Assessment and Prioritisation

AIIC Australian Inventory of Industrial Chemicals

TWA Time-Weighted Average STEL Short Term Exposure Limit

HSNO Hazardous Substances and New Organisms Act 1996

GHS Globally Harmonised System of Classification and Labelling of Chemicals

WHS Work Health and Safety PPE Personal Protective Equipment.

LD₅₀ Median Lethal Dose

LC₅₀ Median Lethal Concentration

EC₅₀ Effective Concentration of a substance that causes 50% of the maximum response after

exposure for a nominated time

NOAEL No Observed Adverse Effect Level NOEC No Observed Effect Concentration

Page 11 of 11 Product: Stihl Fuel Stabiliser

SAFETY DATA SHEET

SECTION 16 – ANY OTHER RELEVANT INFORMATION Continued

ACRONYMS (Continued):

ECHA European Chemicals Agency

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

HCIS Hazardous Chemical Information System
PBT Persistent, Bioaccumulative and Toxic
vPvB Very Persistent and Very Bioaccumulative

LITERATURE REFERENCES AND SOURCES OF DATA:

OECD Guidelines for Testing of Chemicals

Annex I: OECD Test Guidelines for Studies Included in SIDS

Manual for the Assessment of Chemicals Chapter 2 Data Gathering

International Toxicity Testing Guidelines

Hazardous Chemical Information System (HCIS) - Guidance Material for Hazard Classifications

Preparation of Safety Data Sheets for Hazardous Chemicals Code of Practice.

Model Work Health and Safety Regulations.

Model Work Health and Safety Regulations - Transitional Principles

Workplace Exposure Standards for Airborne Contaminants

Australian Dangerous Goods Code 7th Edition

Approved Criteria for Classifying Hazardous Substances [NOHSC:1008 (2004)]

Guidance on the Classification of Hazardous Chemicals under the WHS Regulations

Assigning a Hazardous Substance to a Group Standard

User Guide to the HSNO Thresholds and Classifications

Summary User Guide to the HSNO Thresholds and Classifications of Hazardous Substances

Correlation between GHS and New Zealand HSNO Hazard Classes and Categories

HSNO Control Regulations

Record of Group Standard Assignment

Labelling of Hazardous Substances Hazard and Precautionary Information

Thresholds and Classifications Under the Hazardous Substances and New Organisms Act 1996

Workplace Exposure Standards and Biological Exposure Indices

NICNAS IMAP Human Health Tier II Assessment for Kerosines CAS Number: 64742-47-8 and 64742-94-5

All information contained in this Safety Data Sheet and the health, safety and environmental information are considered to be accurate to the best of our knowledge as of the issue date specified above. The information presented here within, is based upon the product information supplied by the manufacturer. However, no warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this data sheet.

Health and safety precautions and environmental advice noted in this data sheet may not be accurate for all individuals and/or situations. It is the user's obligation to evaluate and use this product safely and to comply with all applicable laws and regulations. The Company accepts no responsibility for any injury, loss or damage, resulting from abnormal use of the material, from any failure to adhere to recommendations, or from any hazards inherent in the nature of the material.